

FIBERGLASS CABLES FOR PULLING WIRES

Fiberglass cables for pulling wires. Diameter 3.8-8 mm, length 15-200 m



Application

- >> Pulling cables and conduits between wells
- >> Pushing cables under roads
- >> Installations in suspended ceilings
- >> Pipes and channels cleaning
- >> Inserting cables into casing pipes

Structure

- >> Fiberglass FRP
- >> High strength and resilience
- >> PE covering
- >> Good sliding characteristics
- >> Protective function
- >> Colour: Yellow
- >> Powder-coated frame in blue
- >> Fiber ending with guide head
- >> Hand-held bracket



Product ID	Diameter [mm]	Length [m]	Dimensions [cm]	Weight [kg]
I-WS-03.015	3.8	15	45x17x55	1.3
I-WS-03.025	3.8	25	45x17x55	1.9
I-WS-03.050	3.8	50	45x17x55	2.4
I-WS-03.075	3.8	75	45x17x55	2.8
I-WS-03.100	3.8	100	45x17x55	3.2
I-WS-04.025	4.5	25	45x17x55	2.0
I-WS-04.050	4.5	50	45x17x55	2.5
I-WS-04.075	4.5	75	45x17x55	3.0
I-WS-04.100	4.5	100	45x17x55	3.5
I-WS-06.050	6	50	55x20x70	3.6
I-WS-06.075	6	75	55x20x70	4.2
I-WS-06.100	6	100	55x20x70	5.2
I-WS-06.150	6	150	55x20x70	7.2
I-WS-06.200	6	200	55x20x70	9.0
I-WS-08.050	8	50	75x20x85	6.4
I-WS-08.100	8	100	75x20x85	9.0

Cable diameter [mm]	Tensile strength [kN]	Crush resistance [kN]	Minimum bending radius [mm]
3.8	3.8	15	80
4.5	10	2	100
6	22	2.4	160
8	38	3	250

Accessories

Pulling eyes, splice connectors



I-WS-LA; I-WS-GL

Cable stockings



I-WS-PJ; I-WS-PD; I-WS-PT

Flexible Guide Head



I-EH