FIBERGLASS CABLES FOR PULLING WIRES

Fiberglass cables for pulling wires. Diameter 8-13 mm, length 100-350 m

Applications:

- Pulling cables and conduits between wells
- Pushing cables under roads
- Installations in suspended ceilings
- Pipes and channels cleaning
- Inserting cables into casing pipes

Structure

- Fiberglass FRP
- High strength and resilience
- PE covering
- Good sliding characteristics
- Protective function
- Colour: Yellow
- Powder-coated frame in blue
- Fiber ending with guide head
- Wheels for functional transport
- Handbreak to lock drum



Product ID	Diameter [mm]	Length [m]	Dimensions [cm]	Weight [kg]
I-WS-08.150	8	150	105x45x105	24
I-WS-08.200	8	200	105x45x105	27
I-WS-08.250	8	250	105x45x105	30
I-WS-09.100	9	100	115x45x125	22
I-WS-09.150	9	150	115x45x125	27
I-WS-09.200	9	200	115x45x125	32
I-WS-09.250	9	250	115x45x125	37
I-WS-09.300	9	300	115x45x125	42
I-WS-11.100	11	100	115x45x125	32
I-WS-11.150	11	150	115x45x125	37
I-WS-11.200	11	200	115x45x125	42
I-WS-11.250	11	250	115x45x125	47
I-WS-11.300	11	300	115x45x125	52
I-WS-13.100	13	100	115x45x125	37
I-WS-13.150	13	150	115x45x125	42
I-WS-13.200	13	200	115x45x125	47
I-WS-13.250	13	250	115x45x125	52
I-WS-13.300	13	300	115x45x125	55
I-WS-13.350	13	350	115x45x125	59

Cable diamater [mm]	Tensile strength [kN]	Crush resistance [kN]	Minimum bending radius [mm]
8	38	3	250
9	45	3.5	320
11	73	4.1	390
13	102	5	500

Accessories

Pulling eyes, splice connectors

I-WS-LA; I-WS-GL

Cable stockings

I-WS-PJ; I-WS-PD; I-WS-PT

Flexible guide heads

I-EH