

Fiber optic multitube duct cables Z-DT.MT.12-72J, 1.5kN, 8mm, G.652D



- ▶ HDPE jacket (black)
- ▶ Multitube structure
- ▶ UV, water resistant
- ▶ Resistance to chemical agents
- ▶ Resistance to substances occurring in duct systems
- ▶ Reinforced by glass fibers
- ▶ Reinforced by central FRP rod
- ▶ Hydrophobic gel in tube
- ▶ Optical fibers G.652D
- ▶ Ripcords

**Application:**

- ▶ Duct systems
- ▶ Distribution networks
- ▶ Campus networks


Technical data	Product ID	Number of fibers	Number of fibers in tube	Number of tubes/fillers	Cable diameter [mm]	Thickness of jacket [mm]	Weight [kg/km]
	Z-DT.MT-12J.1.5KN-6F	12	6	2/4	8	1.1	52
	A-DT.MT-12J.1.5KN-12F	12	12	1/5	8	1.1	52
	A-DT.MT-24J.1.5KN-6F	24	6	4/2	8	1.1	52
	A-DT.MT-24J.1.5KN-12F	24	12	2/4	8	1.1	52
	A-DT.MT-48J.1.5KN-12F	48	12	4/2	8	1.1	52
	A-DT.MT-72J.1.5KN-12F	72	12	6/0	8	1.1	52

Table 1. Fiber optic duct ZTT cables 12-72F, multitube, 1.5kN, G.652D

Mechanical parameters	IEC standard	Z-DT.MT-12-72J.1.5KN
Tensile Strength	IEC 794-1-E1	1500
Crush resistance	IEC 794 -1-E3	1500N/100mm
Impact resistance	IEC 794 -1-E4	20 impacts, 10 Nm
Repeated bending	IEC 794-1-E6	20 [cycles(15xD)], load 150N
Torsion resistance	IEC 794-1-E7	10 cycles 180°, load 120N
UV resistance	ISO 4892/2	✓
Water penetration resistance	IEC 794-1-F5B	✓
Abrasion resistance	IEC 794-1-E2	✓
Temperature cycling test	IEC 794-1-F1	2 thermal cycles in the range of -40°C÷70°C

Table 2. Mechanical parameters of fiber optic duct ZTT cables 12-72F, multitube, 1.5kN, G.652D

- 1 - HDPE jacket
- 2 - Fiberglass
- 3 - Filler
- 4 - Hydrophobic gel
- 5 - Ripcords (x2)
- 6 - Tube with optical fibers
- 7 - Optical fibers G.652D
- 8 - Central FRP rod



Structure of cable (example for 24F (12F/T))

Number	1	2	3	4	5	6
Colour	Blue	Orange	Green	Brown	Grey	White
Number	7	8	9	10	11	12
Colour	Red	Black	Yellow	Violet	Pink	Aquamarine

Table 3. Fiber optic colour coding

- ▶ Storage and transport temperature: -40°C ÷ 70°C
- ▶ Installation temperature: -15°C ÷ 50°C
- ▶ Operation temperature: -30°C ÷ 70°C

